


GRADA INTERNATIONAL

BUILD-IN EXTERNAL LOUVRE W-331

Installation dimensions







All dimensions in mm



Application

The external louvre, type W-331, is designed for wall application, for supply and exhaust of small air volumes in heating, ventilating or airconditioning installations.

The design and the mounting of the Z-shaped blades ensure a weatherproof louvre.

At the back a welded synthetic Insect screen with 1.6 x 1.4 maze is standard provided.

Technical information

Characteristics

- Z-shaped blades under 60°
- blades are clipped into a synthetic blade holder
- blade height 38 mm
- depth 30 mm
- frame and blades 26 mm
- distance of the blades = 33 mm
- total cross-section 1.25/1.50 mm
- 30 mm surface mounting height
- physical passage 43 %
- equipped with a welded synthetic insect screen (1.6 x 1.4 maze x ø 0,24 mm), 69 % free passage
- weatherproof
- available with multiples of 1 mm in length and 10 mm in height min. L = 150 mm, max. L = 2000 mm min. H = 100 mm, max. H = 2000 mm



Construction

- frame and blades in extruded aluminium, natural tone anodised
- when natural tone anodised, synthetic blade holder is coloured light gray
- standard welded synthetic insect screen with 1,6 x 1,4 x Ø 0,24 mm maze, 69 % free passage
- upon request, painted in RAL colour
- upon request:
 - woven aluminium insect screen $(1.8 \times 1.4 \times \emptyset 0.22 \text{ mm})$
 - welded synthetic insect screen (2.8 x 2.8 x Ø 0.25 mm)

Specifications description

Example:

Aluminium build-in external louvre, for small air volumes with fixed Z-shaped blades of extruded profiles. Equipped with a welded synthetic insect screen 1.6 x 1.4 mm maze.

Standard finish: natural tone anodsed. Fixation by dogues.

WB331 Type:

nom. dim. (L x H) ... x ... mm

Fixation

- the louvres are fixed to the wall by meaning of screws (WA or WF)
- the screw holes are already provided for the execution WF
- the louvres are fixed to the wall by dogues (WB)

Delivery possibilities

- WA330: without screw holes, without dogues, without insect screen
- WB330: without screw holes, with dogues, without insect screen
- WF330: with screw holes, without insect screen
- WA331: without screw holes, without dogues, with synthetic insect screen 1.6 x 1.4 mm
- WB331: without screw holes, with dogues and with synthetic insect screen 1.6 x 1.4 mm
- WF331: with screw holes and with synthetic insect screen 1.6 x 1.4
- WA333: without screw holes, without doaues, with aluminium insect screen 1.8 x 1.4 mm
- WB333: without screw holes, with dogues and aluminium insect screen 1.8 x 1.4 mm
- WF333: with screw holes and aluminium insect screen 1.8 x 1.4mm
- WA334: without screw holes, without dogues and with synthetic insect screen 2.8 x 2.8 mm
- WB334: without screw holes, with dogues and synthetic insect screen 2.8 x 2.8 mm
- WF334: without screw holes, without dogues and with synthetic insect screen 2.8 x 2.8 mm

How to order

